NTIA Report 98-346

DGPS Field Strength Measurements at a GWEN Site

J.R. Hoffman
J.J. Lemmon
R.L. Ketchum

U.S. DEPARTMENT OF COMMERCE
William M. Daley, Secretary

Larry Irving, Assistant Secretary
for Communications and Information

March 26, 1998

This Page Intentionally Left Blank

PREFACE

This report is provided by the Institute for Telecommunication Sciences, National Telecommunications and Information Administration, U.S. Department of Commerce, to the Federal Highway Administration (FHWA), U.S. Department of Transportation, in fulfillment of Interagency Agreement Number DTFH61-93-Y-00110.

Management, administration, and technical monitoring of this Agreement have been provided by J.A. Arnold, Electronics Engineer, FHWA.

The authors wish to acknowledge the following individuals from Institute for Telecommunication Sciences for their contributions to this report: M. Cotton for signal strength field measurements; R. DeBolt for DEM maps, three-dimensional topographical maps, and terrain profile plots; N. DeMinco for antenna modeling; Y. Lo for signal strength field measurements.

Certain commercial equipment, instruments, or materials are identified in this paper to specify adequately the technical aspects of the reported results. In no case does such identification imply that the material or equipment identified is the best available for the purpose.

The map in Figure 1 of this report was produced in part by using MapExpert™ software from DeLorne Mapping.

This Page Intentionally Left Blank

CONTENTS

Page

PREFACE iii

FIGURES vii

TABLES ix

ABSTRACT 1

1. PURPOSE 1

2. STRATEGY 1

3. MEASUREMENT SYSTEM 3

4 TRANSMITTER 3

5. MEASUREMENT PROCEDURE 3

6. DATA PROCESSING 6

7. ANALYSIS 6

8. MEASUREMENT RESULTS 6

9. COMPARISON OF MEASUREMENTS WITH MODELS 16

10. SUMMARY 19

11. REFERENCES 20

APPENDIX A: COMPUTATION OF EXPECTED ELECTRIC FIELD STRENGTH . 21

APPENDIX B: SIGNAL FIELD STRENGTH COMPUTATIONS 23

This Page Intentionally Left Blank

FIGURES

Page

Figure 1. Measurement routes 2

Figure 2. Block diagram of the measurement system 4

Figure 3. Signal strength vs. distance for the Apppleton GWEN site coming from Boise, Idaho via Interstate 84 7

Figure 4. Signal strength vs. distance for the Appleton GWEN site going to Bellingham, Washington via Highways 97 and 5 7

Figure 5. Signal strength vs. distance for the Appleton GWEN site going to Medford, Oregon via Interstate 5 8

Figure 6. Signal strength vs. distance for the Appleton GWEN site going to Spokane, Washington via Highway 395 8

Figure 7. Signal strength vs. distance for the Appleton GWEN site going to Boise, Idaho via Highway 20 9

Figure 8. Topography of routes 45 km east and west of the Appleton GWEN site . . . 10

Figure 9. Terrain profile from the transmitter west 45 km to Cascade Locks, Oregon 11

Figure 10. Terrain profile from the transmitter east 45 km to Interstate 84 11

Figure 11. Terrain profile from north to south across the Columbia River Gorge approximately 32 km east of the transmitter 11

Figure 12. Topography for both routes between Boise, Idaho and the Appleton GWEN site 12

Figure 13. Topography for the route between the Appleton GWEN site and Bellingham, Washington 14

Figure 14. Topography for the route between the Appleton GWEN site and Medford, Oregon 15

Figure 15. Topography for the route between the Appleton GWEN site and Spokane, Washington 17

FIGURES (Cont'd)

Page

Figure 16. Signal coverage plot for the Appleton GWEN site showing contours for field strengths of 37.5, 50.0, 60.0, and 70.0 dBμV/m 18

Figure A-1. Signal radiating isotropically into a hemisphere 21

TABLES

Page

Table 1. Spectrum Analyzer Settings 5

Table 2. Field Strength at 10 km and Slope of Least Squares Fit 9

This Page Intentionally Left Blank